

The Number of Free Characters of an Autocorrelation

Eric Rivals

*L.I.R.M.M., CNRS U.M.R. 5506
161 rue Ada, F-34392 Montpellier Cedex 5, France
E-mail: rivals@lirmm.fr*

and

Sven Rahmann

*Max-Planck-Institut für Molekulare Genetik,
Dept. of Computational Molecular Biology,
Ihnestraße 73, D-14195 Berlin, Germany
E-mail: Sven.Rahmann@molgen.mpg.de*

Key Words: autocorrelation, strings, periods, lattice

Algorithm 1: NFC

Input: $n \in \mathbb{N}$, $v \in \Gamma_n$; **Output:** the number of free characters of v ;

```
1 i := 1;
2 while ( $i < n$ ) and ( $v_i \neq 1$ ) do  $i := i + 1$ ;// search for the basic period;
3 if  $i = n$  then return  $n$ ;// no basic period ;
4 if  $i = 1$  then return 1;
5 if ( $i \leq \lfloor \frac{n}{2} \rfloor$ ) then
6   return  $NFC(i + \text{mod}(n, i), v[n - i - \text{mod}(n, i)..n - 1])$ ;
7 else
8   return  $2 \times i - n + NFC(n - i, v[i..n - 1])$ ;
```
